

#1 $A = (10.0)(2.5)$ (2 sig fig)
 $A = 25$

$$\frac{\Delta A}{A} = \frac{\Delta l}{l} + \frac{\Delta w}{w} \quad (\text{error} - 1 \text{ sig fig})$$

$$\frac{\Delta A}{A} = \frac{0.1}{10} + \frac{0.1}{2.5} \quad \Delta A = (0.05 \times 25)$$

$$\frac{\Delta A}{A} = 0.05 \quad \Delta A = 1.25$$

$$\Delta A = \pm 1 \quad (1 \text{ sig fig})$$

$$\therefore A = 25 \pm 1 \text{ cm}^2$$

#2 precise (c) 33.2 ± 0.1
└ smallest variation

accurate (b) 36.5 ± 0.5
└ closest to actual

#3 $\overset{2 \text{ dec.}}{24.31} \pm \overset{1 \text{ sig}}{0.3} - \overset{3 \text{ dec}}{16.765} \pm \overset{1 \text{ sig}}{0.3}$

$$= \boxed{7.55 \pm 0.6}$$

$$\Rightarrow 7.6 \pm 0.6$$

Research
 *matching uncertainty & measurement

#4 $X = A(B-C)$

$$(B-C) = 12.7 \pm 0.2 - 4.3 \pm 0.1$$

$$= 8.4 \pm 0.3$$

$$X = \overset{3 \text{ SF}}{(123 \pm 0.5)} \overset{2 \text{ SF}}{(8.4 \pm 0.3)}$$

$$= 1033.2$$

$$= \underline{1000 \pm 40}$$

$$\frac{\Delta X}{X} = \frac{0.5}{123} + \frac{0.3}{8.4}$$

(1000)

$$\Delta X = 40$$

$$5. \quad V = (6.2)(23)(2.75) \quad (2sf)$$

$$= 392.15$$

$$= \underline{390} \text{ cm}^3$$

Correction steps!

$$\frac{\Delta V}{V} = \frac{0.1}{6.2} + \frac{0.1}{23} + \frac{0.1}{2.75}$$

0.02 0.004 0.04

$$\frac{\Delta V}{390} = \frac{0.0597}{0.06} \rightarrow 0.1$$

$$\Delta V = 390 (0.06)$$

$$\Delta V = \underline{23.4} \text{ cm}^3$$

$$\therefore V = 390 \pm \underline{23} \text{ cm}^3$$

$$V = 390 \pm 23 \text{ cm}^3$$

$$\text{Density } D = \frac{170 \text{ g}}{390 \text{ cm}^3}$$

$$\frac{\Delta D}{D} = \frac{\Delta m}{m} + \frac{\Delta V}{V}$$

$$D = 0.44 \text{ g/cm}^3$$

$$\frac{\Delta D}{0.44} = \frac{0.5}{170} + \frac{39}{390}$$

0.003 0.1

$$D = 0.44 \pm 0.04 \text{ g/cm}^3$$

$$\frac{\Delta D}{0.44} = 0.1003$$

$$\Delta D = 0.44 (0.1)$$

$$\Delta D = 0.04$$

6.

$$\text{Total} = 2.38 + 0.42 + 3.91 + 5.73$$

$$= 12.44 \text{ g}$$

$$\Delta m = 0.05 + 0.05 + 0.05 + 0.05$$

$$\Delta m = 0.20 \text{ g}$$

$$m = 12.44 \pm 0.20 \text{ g}$$